



Product Description:

Concrete Support Systems She Bolt Cone is designed for use where an inner unit is desired and a pass thru she bolt is not practical. The design of the cone provides a tight seal over the concrete tie location, which prevents grout leakage and leaves a clean finished look to the concrete. In addition, the cones set the inside dimension of the formwork and allow for a standard 2" setback from the formwork face to the inner unit.

15 mm She Bolt Cones

Part Number: 106.015.0101

Physical Measurements

Inside Diameter	5/8 in / 15.00 mm
Inner Rod Set Back	2 in / 50 mm
Max. Outside Diam.	2 3/8 in / 60 mm
Min. Outside Diam.	1 1/2 in / 40 mm
Length	4 in / 101 mm
Weight	1.08 lbs / .49 kg

Applications

Working Load	21.9 kips / 97.50 kn
Ultimate Load	43.8 kips / 195.00 kn



Physical Measurements

Inside Diameter	7/8 in / 20.00 mm
Inner Rod Set Back	2 1/2 in / 65 mm
Max. Outside Diam.	2 3/4 in / 71 mm
Min. Outside Diam.	1 3/4 in / 43 mm
Length	5 in / 127 mm
Weight	1.52 lbs / .76 kg

Applications

Working Load	38.0 kips / 172.50 kn
Ultimate Load	76.0 kips / 345.00 kn



3/4 in She Bolt Cone with Coil Thread

Part Number: 106.075.0101

Physical Measurements

Inside Diameter	3/4 in / 19.34 mm
Inner Rod Set Back	2 in / 50 mm
Max. Outside Diam.	2 3/8 in / 60 mm
Min. Outside Diam.	1 1/2 in / 40 mm
Length	4 in / 101 mm
Weight	1.08 lbs / .49 kg

Applications

Working Load	18.0 kips / 80.15 kn
Ultimate Load	36.0 kips / 160.30 kn



Concrete
Support Systems

2770 South Horseshoe Drive
Suite 4, Naples, Florida 34104

p: 239.330.7614
f: 239.330.7958

info@concretesupportusa.com
www.concretesupportusa.com