



Product Description:

Concrete Support Systems Euro Thread Strong She Bolt has the highest safe working load in the world. With a 2:1 safety factor we are able to utilize the full strength of the hot rolled Euro Rod inner unit. This innovative design provides 15% more strength than conventional euro thread she bolts, this means higher allowable placement pressures and fewer ties. The she bolt has a thread design of 2.5 inches per thread and continuous flats which allow for application of multi-release tool in order to remove the she bolt from the concrete wall.

15 mm Strong Pass Thru She Bolts

Part Number: 106.015.1000

Physical Measurements

Inside Diameter	5/8 in / 15.00 mm
Inner Rod Set Back	2 in / 50 mm
Outside Diameter	1 1/8 in / 28.79 mm
Length	19 1/4 in / 486 mm
Weight	1.30 lbs / .59 kg

Applications

Working Load	21.9 kips / 97.50 kn
Ultimate Load	43.8 kips / 195.0 kn



Physical Measurements

Inside Diameter	7/8 in / 20.00 mm
Inner Rod Set Back	2 in / 50 mm
Outside Diameter	1 3/8 in / 35.08 mm
Length	19 1/4 in / 486 mm
Weight	2.30 lbs / 1.04 kg

Applications

Working Load	38.0 kips / 172.50 kn
Ultimate Load	76.0 kips / 345.0 kn

