



Product Description:

Concrete Support Systems Euro Thread Standard Taper Tie can be used with any form system. These pass thru taper ties are machined from solid high strength steel rods. The threads of the taper tie are a standard full round Euro Thread and the end is machined into a square to permit the application of a wrench for product removal.

16 in x 15 mm Standard Taper Ties

Part Number: 108.015.0016

Physical Measurements

Thread Diameter	5/8 in / 15.00 mm
Taper length	16 in / 406 mm
Diameter	Max: 7/8 in Min: 3/4 in / Max: 20 mm Min: 19.20 mm
Overall Length	41 in / 1041 mm
Weight	11.8 lbs / 5.31 kg

Applications

Working Load	18.8 kips / 83.70 kn
Ultimate Load	37.6 kips / 167.40 kn



Physical Measurements

Thread Diameter	5/8 in / 15.00 mm
Taper length	24 in / 610 mm
Diameter	Max: 7/8 in Min: 3/4 in / Max: 20 mm Min: 19.20 mm
Overall Length	45 in / 1143.0 mm
Weight	13.5 lbs / 6.08 kg

Applications

Working Load	18.8 kips / 83.70 kn
Ultimate Load	37.6 kips / 167.40 kn



32 in x 15 mm Standard Taper Ties

Part Number: 108.015.0032

Physical Measurements

Thread Diameter	5/8 in / 15.00 mm
Taper length	32 in / 813 mm
Diameter	Max: 7/8 in Min: 3/4 in / Max: 20 mm Min: 19.20 mm
Overall Length	53 in / 1346.0 mm
Weight	15.2 lbs / 6.84 kg

Applications

Working Load	18.8 kips / 83.70 kn
Ultimate Load	37.6 kips / 167.40 kn



Concrete
Support Systems

2770 South Horseshoe Drive
Suite 4, Naples, Florida 34104

p: 239.330.7614
f: 239.330.7958

info@concretesupportusa.com
www.concretesupportusa.com

16 in x 20 mm Standard Taper Ties

Part Number: 108.020.0016

Physical Measurements

Thread Diameter	7/8 in / 20.00 mm
Taper length	16 in / 406 mm
Diameter	Max: 1 1/4 in Min: 1 in / Max: 31.75 mm Min: 25.40 mm
Overall Length	41 in / 1041.0 mm
Weight	4.65 lbs / 2.09 kg

Applications

Working Load	37.5 kips / 166.95 kn
Ultimate Load	75.0 kips / 333.90 kn



Concrete
Support Systems

2770 South Horseshoe Drive
Suite 4, Naples, Florida 34104

p: 239.330.7614
f: 239.330.7958

info@concretesupportusa.com
www.concretesupportusa.com

Physical Measurements

Thread Diameter	7/8 in / 20.00 mm
Taper length	24 in / 610 mm
Diameter	Max: 1 1/4 in Min: 1 in / Max: 31.75 mm Min: 25.40 mm
Overall Length	45 in / 1143.0 mm
Weight	5.81 lbs / 2.61 kg

Applications

Working Load	37.5 kips / 166.95 kn
Ultimate Load	75.0 kips / 333.90 kn



32 in x 20 mm Standard Taper Ties

Part Number: 108.020.0032

Physical Measurements

Thread Diameter	7/8 in / 20.00 mm
Taper length	32 in / 813 mm
Diameter	Max: 1 1/4 in Min: 1 in / Max: 31.75 mm Min: 25.40 mm
Overall Length	53 in / 1346.0 mm
Weight	7.0 lbs / 3.15 kg

Applications

Working Load	37.5 kips / 166.95 kn
Ultimate Load	75.0 kips / 333.90 kn



Concrete
Support Systems

2770 South Horseshoe Drive
Suite 4, Naples, Florida 34104

p: 239.330.7614
f: 239.330.7958

info@concretesupportusa.com
www.concretesupportusa.com